

HT 4060 High temperature thermocouple up to 1800°C

Protection tube	
Construction	Gastight ceramic
Insertion length	Customer to specify
Diameter	15x2.0mm standard, Other diameters possible
Material	Gastight Ceramic 710 (C799) 99.7% Aluminium oxide, Other types of ceramic possible
Temperature	1800°C maximum (0.5mm wires type B) 1600°C maximum (0.35mm type B wires or 0.5mm wires type R/S) 1350°C maximum (0.35mm wires type R and S)
Process connection	Sliding flange model, other executions possible for example a welded ANSI or DIN flange
Inner tube (optional)	
Material	Gastight ceramic 710 (C799) or Sapphire
Connection head	
Model	Type A , other connectionheads possible
Material	Aluminium or Stainless Steel
Cable entry	M20x1.5 standard, other threads possible
Head extention	
Material	Steel standard, other materials possible
Diameter	32mm standard, other diameters possible
Length	200mm standard, other lengths possible
Measuring insert	
Insulation	Ceramic insulation rod
Calibration	B, R or S
For duplex	BB, RR or SS
Wire size	0.35mm or 0.5mm
Accuracy	According to IEC 60584-1
Options	
Swing-Cover head	DAN, transmitter direct mounted on measuring insert
High Swing-Cover head	DAN-H, transmitter in cover, insert with ceramic block

